

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 664)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 4, 5, 8, & 9, mkd. T 21 S S 4 on NE, R 7 W S 9 on SE, S 8 on SW, S 5 on NW face, with 4 notch(es) on E & 5 on S edges; from which
V. Maple, 6" dia. bears N.38°E. 10 lks. mkd: T21S R7W S4 BT
Cedar, 30" dia. bears N.50°W., 29 lks. mkd: T21S R7W S5 BT
Cedar, 30" dia. bears S.60°E., 40 lks. mkd: T21S R7W S9 BT
Fir, 30" dia. bears S.18°W., 16 lks. mkd: T21S R7W S8 BT.

Wilford N. Haines, #239 & Leo Martin - For: Harold Woolley - Filed Jan. 21, 1958 - M 8-31

Set Lot Marker from original BT.

Douglas Co. Surveyors Office - Milo Godfrey & Crew - Nov. 9, 1962 - C.S. File 49/20-17

Found - Cedar, 40" dia. S.60°E., 26.4 ft. previously opened, scribing visible on old face, "BT S9 T21S R7W"
45" Cedar N.50°W., 12.5 ft. (19 lks., not 29 lks.) shows scar. Did not open.
No trace of NE or SW BTs
Set brass cap at cor. mkd: COUNTY SURVEYORS T21S R7W $\frac{S}{S} \frac{5}{8} | \frac{S}{S} \frac{4}{9}$
OFFICE 1962
Reblaze & scribe 2 orig. BTs:
40" Cedar S.60°E., 26.4 ft., mkd: T21S R7W S9 CS BT
45" Cedar N.50°W., 12.5 ft., mkd: T21S R7W S5 CS BT
New BTs- 12" D.Fir N.79°E., 79.1 ft., mkd: T21S R7W S4 CS BT
No suitable tree available SW of corner.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J Flause - Terrie Franssen - 4/7/1992 - C.S. 64/24-11

Found - A 2½" dia., DCSO brass cap on a 1½" O.D. iron pipe, protruding 5" above ground.
A Haines T-iron protruding 9" above ground. T-iron bears S.16°W., 8.4 ft. from DCSO BC/IP. Haines T-iron was set at an intersection of orig. distances. Orig. BT bears S.81°E., 26.4 ft. & N.23½°W., 19.1 ft.
FD BTs - Brg's & dists. taken from 1962 DCSO BC/IP
30" now 44" dia., Cedar with a previously opened orig. blaze scribing visible "T22R & a partially healed rescribing "SR7W S9". BT bears S.60°E., 26.4 ft. (agrees w/rec) continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

30" now 50" dia. Cedar a partially healed rescribing illegible scribing visible, bears N.50°W., 12.5 ft. (agrees w/1962)
12" now 18" dia., D.Fir with a fully healed single blaze, bears N.79°E., 78.5 ft. (Rec. N.79°E., 79.1 ft. is to cut trunk) 1962
Note - Corner lies approx. 150 ft. East of Smith River.