

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 324700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 33 only, T20-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 573)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face; from which

A Fir 30" dia., bears S.39°W., 38 lks. dist. mkd. ¼ S BT.

A Fir 36" dia., bears N.82°W., 82 ks. dist. mkd. ¼ S BT.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1159, surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18038)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

T 20 S R 7 W

¼ S 33

T 21 S R 7 W

1984

from which

A Fir 8" dia., bears N.12½°E., 3½ lks. dist. mkd. ¼ S33 BT on bark.

An Alder 8" dia., bears N.82½°W., 43 lks. dist. mkd. ¼ S33 BT on bark.