

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 632)

Set ¼ sec. post, from which
A Fir 40" dia., bears N.15°E., 7 lks. dist.
A Fir 8" dia., bears S.5°E., 59 lks. dist.

Wilford N. Haines - For: Woolley Logging - Dec. 1963 - M 27-16

Set 1" x 1" x 36" T. Iron.
No bearing trees set.

Ted Baker - For: Seneca Jones Timber Co. - 1/2003 - M141-58

The "T" iron set by Haines marking the ¼ corner of sec. 33 along the north boundary was found to be out of position so we set iron pins with alum. caps at the true position.

Set - 5/8"x36" iron pins with 2½" alum. cap
16" Fir N.18°W., 24.3'
12" Fir N.53°E., 39.0'
Haines "T" iron bears N.78°E., 10.49'

Note - All BTs are scribed & painted red, distances to BTs are center measure.