

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

|       |       |             |       |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 659)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which  
V.Maple, 8" dia., bears N.53°W., 5 lks., mkd: ¼ S BT.  
Fir, 30" dia., bears S.7°W., 53 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13514-5)

-----  
Point for the ¼ sec. cor. of secs. 28 & 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" diam., 22" in the ground, with brass cap marked:

¼  $\frac{S\ 28}{S\ 33}$   
T 21 S R 7 W  
1964

from which

A W.Fir, 6" dia., bears N.54°E., 14 lks., mkd: ¼ S28 BT.  
A Hemlock, 7" dia., bears S.33°E., 51 lks., mkd: ¼ S33 BT.

BLM Dependent resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, under Group #1318, surveyed May/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18315-6)

-----  
The ¼ sec. cor. of secs. 28 & 33, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass ca mkd.

T 21 S R 7 W

¼  $\frac{S\ 28}{S\ 33}$   
1964

from which the remaining BT mkd. by Brooks & Jelley

A W.Fir, 12" dia. bears N.54°E. 14 lks. with healed blaze. and a new bearing tree

A Fir, 6" dia. , bears S.38¼°E., 34½ lks., mkd. ¼ S33 BT.  
From this point, United States Geological Survey triangulation station "TOM FOLLEY 1953", bears S.79°03'00" E. 370.130 chs.

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent - 4/2018 - C.S. File 65/101-29

-----  
Found - BLM brass cap (properly mkd)  
18" W.Fir N.54°E., 9.2 ft. good scar  
18" Fir S.38¼°E., 22.8 ft good scar

cont.

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

New - 12" Fir S.1°E., 13.4 ft. scribed ¼ S33 BT.  
15" S.42°W., 16.0 ft. scribed ¼ S33 BT.  
6' Steel post 1.3 East - 1.0 West - 1.0 North  
Note - 15½°E.