

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 340240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, under Group #1318, surveyed May/Nov. 1986 - (DCS0 records Vol. 48 Page(s) 18316)

-----  
Point for the center ¼ sec. cor. of sec. 28, at intersection with the E. and W. center line.  
Set an iron post, 28" long, 2½" diam., 23" in the ground, with brass cap mkd.  
T 21 S R 7 W  
C ½ S 28  
1986

from which  
A fir, 5" dia., bears S.34°W., 138½ lks., mkd. C¼ S28 BT.  
A fir, 50" dia., bears N.12°W. , 19 lks., mkd. C¼ S28 BT.  
From this point, a point of no known record, bears S.60°30'W. 0.093 chs., monumented with an iron rod, 1¼" dia., firmly set, projecting 6" above ground.

David Edwards - For: Roseburg Resources - Jan. 2025 - M184-49

-----  
Found - Brass cap  
A 17" dia. fir bears S.34°W.91.4'.  
A 50" dia. fir bears N.12°W.12.5'.  
Both with healed blaze.  
Set - Set 5.5' steel posts 2'E. on line and 2'N.

David Edwards - For: Roseburg Resources - Dec. 2025 - M186-60

-----  
Found ok per M184-49