

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 660)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 30" dia., bears N.35°W., 36 lks., mkd: ¼ S BT.
Fir, 30" dia., bears S.48°E., 12 lks., mkd: ¼ S BT.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13517)

Point for ¼ sec. cor. of secs. 21 & 28, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼ $\frac{S\ 21}{S\ 28}$
T 21 S R 7 W
1964

from which
A Fir, 10" dia., bears N.33°E., 11 lks., mkd: ¼ S21 BT.
A Fir, 11" dia., bears S.13¼°E., 15 lks., mkd: ¼ S28 BT.

Fd. & used on BLM Dependent resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, under Group #1318, surveyed May/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18317)

David Edwards - For: Roseburg Resources - Dec. 2025 - M186-60

Found - 20" diam. Fir bears N.33°E. 7.3 ft.
18" diam. Fir bears S.13¼°E. 9.9 ft.
Both with healed blaze.
New - 5.5 ft. steel posts are set 2 ft. S.2°W. and 2 ft. west on line.