

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Page(s) 662)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked $\frac{1}{4}$ S on N face; from which
Fir, 40" dia., bears N.64°E., 13 lks., mkd: $\frac{1}{4}$ S BT.
Hemlock, 5" dia., bears S.10°W., 19 lks., mkd: $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - C. Putman - July 9, 1959 - C.S. File 49/20-9

Found - Fir tree, now 54", N.64°E., 8.6 ft., old bark scribing found "BT $\frac{1}{4}$ S"
No trace of other old BT
At corner set iron pipe with brass cap mkd: COUNTY SURVEYORS
 $\frac{1}{4}$ S 16 OFFICE 1959
S 21
Blaze & scribe following trees:
12" Hemlock, N.78°W., 27.4 ft. mkd: " $\frac{1}{4}$ S16 CS BT"
14" Hemlock, S.3°E., 34.2 ft. mkd: " $\frac{1}{4}$ S21 CS BT"

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2619, Surveyed March/May 2011 - (DCSO records BLM Plat T21-7W 2012-1 & Vol. 58 Pages 22943-4)

The $\frac{1}{4}$ sec. cor. of secs. 16 & 21, perpetuated by Byron, in 1959, monumented with an iron post, 1 $\frac{1}{4}$ " dia., firmly set, projecting 13" above ground, with a brass cap (properly) mkd: from which the remaining orig. BT
A fir, 65" dia., bears N.65°E., 8.6 ft. with axe marks visible.
and a BT mkd. by Byron
A hemlock, 20" dia., bears S.3°E., 34.2 ft. with a healed double blaze.