

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4 only

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 556-57)

Set post 4" dia., 4 ft. long, 24" in ground for ¼ sec. cor. mkd. ¼ S on N. face, from which

- A Fir 24" dia., bears N.13°W., 44 lks. dist. mkd. ¼ S BT.
- A Fir 6" dia., bears S.63°W., 13 lks. dist. mkd. ¼ S BT.

Fd. OK and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 573)

Wilford N. Haines, #239 - For: Harold Woolley - Filed Jan. 21, 1958 - M 8-31

Set Lot Marker from original BTs to SW.
Scribed- 30" Fir S.08°W., 35.4 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1159, surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18037-38)

The ¼ sec. cor., perpetuated and recorded by Haines in 1958, monumented with a 1" T shaped iron rod, firmly set, projecting 4" above ground, from which the remains of the original bearing trees:

- A decayed Fir stump 44" dia., bears N.13°W., 44 lks. dist., no marks visible.
- A burned Fir stump, 40" dia., bears S.63°W., 13 lks. dist. no marks visible.

and the remains of a bearing tree mkd. by Haines:

- A sawed Fir stump 69" dia., bears S.8°W., 35½ lks. dist. with healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron rod, with brass cap mkd:

T 20 S R 7 W

¼ S 4

T 21 S R 7 W

1984

from which new bearing trees:

- A Fir 10" dia., bears S.7 3/4°E., 16 lks. dist. mkd. ¼ S4 BT.
- A Fir 8" dia., bears S.83½°W., 41 lks. dist. mkd. X BT.