

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 374100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 and 4 only, T22-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1546)

At point of intersection, 5.10 chs. West of corner for secs. 33 & 34, T21S R7W, I Set a Dogwood post, 3 ft. long, 4" sq., 24" in the ground for a closing cor. of secs. 3 and 4, mkd. C C T22S R7W on S.; S3 on E.; and S4 on W. faces; with 3 grooves on E. and W. faces; from which

A Fir 48" dia., bears S.20°E., 57 lks. dist. mkd. T22S R7W S3 BT.

A Dogwood 12" dia., bears S.42°W., 63 lks. dist. mkd. T22S R7W S4 BT.

Wilford N. Haines - For: Harold Woolley - March 1957 - M 4-52 and Field Book H-178

Found original corner.
Set a 1" x 36" T rod at corner with brass cap inscribed "Wilford N. Haines Survey Point #239".

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - May/June 1962 - C.S. File 52/14-110

Found - Haines T Iron and cap.
Fir, now 64", S.20°E., 37.6 ft., cut open and found good scribing "S" on old face.
Dogwood, down and badly rotted, S.42°W., 41.6 ft.
Found burl wood but center rotted away. No scribing or old face found.

Blaze and rescribe (in wood)
64" D.Fir S.20°E., 37.6 ft. mkd. T22S R7W CC S3 CS BT.

New BT - 12" Red Cedar S.17°W., 41.8 ft. mkd. T22S R7W S4 CC CS BT.

Douglas Co. Surveyors Office - Gary C. Commons; Peter L. Earle, crew - Jan. 29, 1975 - C.S. File 57/17-13

Found - Haines T iron and cap.
A 12" Red Cedar now 18", S.17°E., 41.8 ft., scribe visible.

D.Fir 64", S.20°E., 37.6 ft. Is now blown down.
Set 1" x 30" iron pipe with brass cap mkd:

(Cont. Next Page)

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 374100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 and 4 only, T22-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

County Surveyors Office
T 21 S R 7 W
S 33
S 4 | S 3
T 22 S R 7 W
CC
1975

New BT - A 6" Hemlock, S.48°E., 43.2 ft. mkd. CC T22S R7W S3
CS BT.
We set Haines T Iron alongside the cap. Corner lies in bottom
of draw, center line N-S.

Ted Baker - For: Seneca Jones Timber Co. - 1/2003 - M141-58

Found - 1975 2½" Douglas Co. Brass cap 11.05' north of line.
30" Cedar S.17°W., 41.8' (scar vis) {Rec. S.17°E.}
11" Hemlock, S.48°E., 43.2' (scar vis)

Troy Rambo - For: Seneca Jones Timber Co. & Roseburg
Resources Co. - 1/2011 - M161-71

Set - Ammended corner, 5/8"x36" rebar with 2½" alum. cap, from
which
DCSO BC 11.05' north of line.
12" GF (Hemlock) w/healed face - bears S.52°E. 36.5 ft
35" Cedar w/a healed face - bears S.24°W., 30.7 ft.
A steel post - bears West 1.2 ft.
Note- The BTs also reference the closing corner.

2