

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 649)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which  
Fir, 40" dia., bears N.12°E., 30 lks., mkd: ¼ S BT.  
Laurel, 16" dia., bears N.76°W., 50 lks., mkd: ¼ S BT.

-----  
Wilford N. Haines - For: Harold Woolley - March 1957 - M 4-72

-----  
Found - Orig. Fir BT  
Set - 1"x36" ⊥ rod at corner point with brass cap  
inscribed, "Wilford N. Haines, Survey Point #239"  
12" Fir, S.11°W., 7.1 ft.

-----  
David Edwards - For: Seneca Jones Timber Co. - 1/2002 -C.S.  
File 65/41-3

-----  
Found - T-iron per M4-52  
A 25" Fir bears S.11°W., 7.1 ft.  
New BT - 12" Fir bears S.4°E., 19.3 ft.

-----  
David Edwards - For: Roseburg Resources - May 2019 - M175-52

-----  
Found - T-Iron per M4-52 in poor condition. We replace with rebar/cap.  
A 16" Fir bears S.4°E., 19.3'  
A 29" Fir bears S.11°W., 7.1'  
Both with healed blaze.  
A six ft steel post is set 2 ft north.