

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 651)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 21, 22, 27, & 28, mkd. T 21 S S 22 on NE, R 7 W S 27 on SE, S 28 on SW, S 21 on NW face, with 3 notches on E & 2 notches on S edges; from which  
    Fir, 40" dia. bears N.80°E., 53 lks. mkd: T21S R7W S22 BT.  
    Fir, 40" dia. bears S.10°W., 34 lks. mkd: T21S R7W S28 BT.  
    Fir, 40" dia. bears N.52°W., 13 lks. mkd: T21S R7W S21 BT.  
    Dogwood, 12" dia., bears S.73°E., 97 lks., mkd: T21S R7W S27 BT.

Wilford Haines - For: E.G. Whipple & Woolley Logging - Feb. 1961 - M20-19

-----  
Found - 3 Orig. Fir BTs  
Set - 1"x1"x36" T. Iron for corner.

BLM dependent resurvey by Floyd A. Brooks & James E. Jelley, Cadastral Surveyors, under group 350 & 536, surveyed May/June 1964 - (DCSO records Vol. 32 Page(s) 13516-7)

-----  
The cor. of secs. 21, 22, 27, and 28, established by Wheeler in 1883; remonumented by Haines, in 1961, with a 1" "T" iron, 36" long, driven 24" in the ground, from which the remaining original bearing trees:

    A fir, 70" dia. bears N.80°E. 53 lks. with a healed blaze.  
    A fir, 55" dia. bears S.10°W. 34 lks. with a healed blaze.  
    A fir, 56" dia. bears N.52°W. 13 lks. with a healed blaze.  
    This tree remarked BT S21 T21S R7W by Haines on a bark blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

    T 21 S R 7 W  
    S 21 | S 22  
    S 28 | S 27  
    1964

from which new bearing trees

    A hemlock, 15" dia., bears N.68¾°E., 48 lks., mkd. T21S R7W S22 BT.  
    A cedar, 25" diam., bears S.28°E., 93 lks., mkd. T21S R7W S27 BT.  
    A cedar, 43" diam., bears N.28°W., 79 lks., mkd. T21S R7W S21 BT.

Deposit the Haines' monument alongside the iron post.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, under Group #1318, surveyed May/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18315)

-----  
The cor. of secs. 21, 22, 27, & 28, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, alongside of which is a 1" T shaped iron rod, firmly set, projecting 8" above ground. The brass cap is mkd.

T 21 S R 7 W  
S 21 | S 22  
S 28 | S 27  
1964

from which the remains of the original bearing trees  
A fir, 72" dia., bears N.80°E., 53 lks., with healed blaze  
A sawed fir stump, 52" dia., bears S.10°W., 34 lks., with healed blaze.  
A fir, 58" dia., bears N.52°W., 13 lks., with healed blaze and scribe marks BT S21 T21S R7W visible on bark.  
and the remains of bearing trees mkd. by Brooks and Jelley  
A hemlock, 19" dia bears N.68¾°E. 48 lks with healed blaze  
A sawed cedar stump, 28" dia., bears S.27°E., 93 lks., with scribe marks S R7W visible on partially healed blaze. (Record, S.28°E.)  
A cedar, 43" dia., bears N.28°W., 57 lks., with scribe marks T21S R7W S21 BT visible on partially healed blaze. (Record, 79 lks.)  
and a new bearing tree  
A maple, 13" dia., bears S.44°W., 76½ lks., mkd. T21S R7W S28 BT.

FD. ok on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20645-6)

Ronald L. Rice, Ward NW - 7/2008 - C.S. File 65/63-24

-----  
Condition report only  
Found - 3¼" brass cap dated 1964 w/the following accessories  
72" D.Fir bears N.80°E., 35.0' - healed face.  
47" W. Red Cedar bears N.28°W., 31.7' - healed face.  
22" Hemlock bears N.68¾°E., 31.7' - healed face.  
58" D.Fir snag bears N.52°W., 8.6' - healed face.  
Note - Corner has steel post adjacent to it.  
All BTs have red painted bands & yellow tags.  
Dec. 17°East.