

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 2 Page(s) 652)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 15, 16, 21, & 22, mkd. T 21 S S 15 on NE, R 7 W S 22 on SE, S 21 on SW, S 16 on NW face, with 3 notches on S & E edges; from which
Hemlock, 14" dia., bears N.8°E., 21 lks., mkd: T21S R7W S15 BT.
Hemlock, 12" dia., bears N.25°W., 47 lks., mkd: T21S R7W S16 BT.
Hemlock, 20" dia., bears S.48°W., 39 lks., mkd: T21S R7W S21 BT.
Fir, 30" dia. bears S.18°E., 56 lks. mkd: T21S R7W S22 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - C. Putman - July 9, 1959 - C.S. File 49/20-10

Found - Hemlock snag, now 20" N.8°E., 13.9 ft. Scribe mks. "21SR" plainly visible in formerly chopped open scar. Ring count shows this to have been scribed approx. 70 to 75 years ago. (Orig. survey 1883) Old rotten stumps to SE & SW that fit notes of orig. BTs. (Distances measured on slope) No scribing fd. on these stumps.
No trace of NW BT.

At corner set iron pipe with brass cap mkd: County Surveyors
S 16 | S 15 T21S R7W Office 1959
S 21 | S 22

Blazed & scribe new trees:
20" Hemlock N.80½°W. 18.3 ft. mkd: T21S R7W S16 CSBT
14" R.Cedar S.63°E., 8.2 ft. mkd: T21S R7W S22 CS BT
8" Hemlock N.38°E., 20.0 ft. mkd: T21S R7W S15 CS BT
10" Cedar S.72°W., 38.8 ft., mkd: T21S R7W S21 CS BT