

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 2 Page(s) 653-4)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 15, 16, 9, & 10, mkd. T 21 S S 10 on NE, R 7 W S 15 on SE, S 16 on SW, S 9 on NW face, with 3 notches on E & 4 notches on S edges; from which
 Fir, 36" dia. bears N.6°E., 27 lks., mkd: T21S R7W S10 BT.
 Fir, 20" dia. bears S.60°E., 27 lks. mkd: T21S R7W S25 BT.
 Fir, 40" dia. bears S.57°W., 27 lks. mkd: T21S R7W S16 BT
 Fir, 36" dia. bears N.69°W., 44 lks., mkd: T21S R7W S9 BT.

Wilford Haines - July 27, 1955 - C.S. file 42/3 & M1-68

Set - A 1"x1"x36" angle iron with brass cap inscribed Wilford
 N. Haines #239.
Corner set from old BTs

Wilford Haines - Nov. 30, 1965 - C.S. file 51/309-3

Found - "T" iron
 Orig. BTs now stump.
New BTs- 6" R.Cedar N.28°W., 90.5 ft.
 14" R.Cedar N.8°E., 106.2 ft.
 7" Hemlock S.58°W., 70.0 ft.
 26" Fir S.23½°W., 113.8 ft.