

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #514, dated Aug. 27, 1884 - (DCSO records Vol. 2 Pages 655-6)

-----  
Set post, 6x6", 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 3, 4, 9, & 10, mkd. T 21 S S 3 on NE, R 7 W S 10 on SE, S 9 on SW, S 4 on NW face, with 3 notches on E & 5 on S edges; from which

- Fir, 36" dia., bears N.70°E., 95 lks. mkd: T21S R7W S3 BT.
- Fir, 36" dia. bears S.81°E., 64 lks. mkd: T21S R7W S10 BT.
- Fir, 10" dia. bears S.71°W., 40 lks. mkd: T21S R7W S9 BT.
- Fir, 20" dia. bears N.18°W., 107 lks., mkd: T21S R7W S4 BT

-----  
Wilford N. Haines, #239 & Leo Martin - For: Harold Woolley - Filed Jan. 21, 1958 - M 8-31

-----  
Set Lot Marker from original BTs.

-----  
Wilford N. Haines, #239 - For: Woolley Logging - April 7, 1965 - M 29-67

-----  
Found - T iron  
Orig. 10" Fir, now 20" S.71°W., 40 lks., scribed BT in wood below old bark scribe.  
New BTs- 20" Fir S.24°E., 47.4 ft.  
14" Hemlock N.75°W., 34.0 ft.

-----  
Les Roberts- For: Seneca Jones Timber Co. - March 10, 2000 -M 134-37

-----  
Found - Haines 1958 "T" iron set on M 8-31.  
20" Fir stump, S.71°W., 26.4' (scribe vis) OBT  
20" Fir stump, S.24°E., 47.5' (scribe vis) 1965  
Set - 6" Hemlock N.60°W. 9.4' (scribe/metal washer/painted red)  
6" Fir, N.22°E., 7.8' (scribed/metal washer/painted red)  
6" Fir S.59°E., 13.5' (scribed/metal washer/painted red)  
8" Fir, S.46°W., 3.6' (scribed/metal washer/painted red)