

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 34; and 3 of T22-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 632)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.10°W., 36 lks. dist.
A Fir 48" dia., bears N.25°W., 81 lks. dist.

Wilford N. Haines - For: Harold Woolley - March 1957 - M 4-52

Point for corner located by proportionate measurement
Set 1" x 36" T rod at corner point with brass cap inscribed "Wilford N. Haines Survey Point #239", from which
26" Fir N.44°00'E., 5.6 ft.
26" Fir S.9°30'W., 9.5 ft.

Fd. OK, May 1962, DCSO, M. Godfrey, C.S. File 52/14-6

David Edwards - For: Seneca Jones - 1/2002 - M 136-69 & C.S. File 65/41-3

Found - Both BTs down.
Set - 5/8" steel rod 46" long, set Alum. cap mkd. per Manual on rod.
6' steel posts North, South, East, & West. All at 5.0 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/16/2002 - C.S. File 66/32-28

Found - 2½" dia., alum. cap on a 5/8" iron rod, protrudes 9" out of ground, marked:
T21S R7W
¼ $\frac{S\ 34}{S\ 3}$
T22S R8W
LS 2339
2002
26" dia., 1957 BTs now 29" down D.Firs. Root holes agree well with record. "N.44°E., 5.6 ft. & S.9½°W., 9.5 ft."
2002 Metal fence post set at 5 ft. North, South, East & West.
New - 4" dia., D.Fir double blazed & scribed "X BT" bears N.2°E., 61.3 ft.
25" dia., D.Fir double blazed & scribed "¼ S34 CS BT" bears N.87°W., 129.8 ft.
Compass decl. 17½°E.