

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 650)

-----  
A Fir, 3" dia., for 1/4 sec. cor., marked 1/4 S on N face; from which

Fir, 4" dia., bears N.25°W., 4 lks., mkd: 1/4 S BT.

Fir, 4" dia., bears S.44°E., 8 lks., mkd: 1/4 S BT.

-----  
Wilford Haines - For: Woolley Logging Co. - 1963 - M 27-32

No trace of orig. corner.

Set - 1"x1"x36" T iron from which:

10" D.Fir N.37°E., 5.0 ft.

7" D.Fir S.67°E., 5.7 ft.

-----  
Fd. Ok by L. Roberts, 1/30/1997 - C.S. File 65/13-4

Fd. Ok by L. Roberts, 5/1999 - M131-62

-----  
BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20642-3)

-----  
The 1/4 sec. cor. of secs. 27 & 34, reestablished by proportionate measurement by Haines, in 1963, and is accepted as the corner; monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 4 ins. above ground, from which the remains of a bearing tree mkd. by Haines

A fir snag, 10" dia., bears N.34 1/4°E., 5.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T 21 S R 7 W

1/4  $\frac{S\ 27}{S\ 34}$

1999

and new bearing trees

A hemlock, 7" dia. bears N.50 1/2°E., 10.4 ft. mkd. 1/4 S27 BT.

A hemlock, 16" dia. bears N.26 1/2°W., 6.2 ft. mkd. 1/4 S27 BT.

Each new bearing tree has a 2 1/2" X 1/4" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

-----  
continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

David Edwards - For: Roseburg Resources - May 2019 - M175-52

-----

Found - BLM brass cap  
A 16" Hemlock bears N.50½°E., 10.4' w/healed blaze  
No other previous BTs fd.  
New - A 5' Fir scribed "¼ S34 BT" bears S.53°W., 29.9'  
Set - A six ft steel post 2 ft south.