

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 651)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 36" dia., bears N.78°W., 11 lks., mkd: ¼ S BT.
Fir, 30" dia., bears S.15°E., 14 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey & S. Bilow - Nov. 25, 1957 - C.S. File 49/20-1

Found - Both Orig. BTs:
Orig. 30" now 46" R.Fir. I open & find good scribing "4". Rec. bearing S.15°E. I find should be S.15°W. Checks record distance.
Orig. 36" now 50" R.Fir shows old bark scribe marks "1/" checks rec. dist. & bearing N.78°W., 7.2 ft.
Set brass cap at corner mkd: ¼ S22/S27 T21S R7W County Surveyors Office 1957.
New BTs- 8" R.Fir N.23°W., 33.8 ft., mkd: ¼ S22 CS BT
5" R.Fir S.45°W., 1.1 ft., mkd: ¼ S27 CS BT

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20644-5)

The ¼ sec. cor. of secs. 22 & 27, perpetuated by Byron, in 1957; monumented with an iron pipe, 1¼" diam., badly bent out of position by the base of the SW. bearing tree, mkd. by Byron, with brass cap (properly) mkd.
from which the remains of the original bearing tree
A roothole, bears S.9¼°W., 9.2 ft., with decayed fir alongside, 42" diam., no marks visible. (Record, S.15°E.)
A broken fir stump, 64" diam., bears N.82¼°W., 8.4 ft., no marks visible. (Record, N.78°W., 7.3 ft.)
and bearing trees mkd. by Byron
A fir, 28" diam., bears S.4¼°W., 1.5 ft., with a healed double blaze.
A fir, 37" diam., bears N.23½°W., 33.1 ft., with a healed double blaze.
and a new reference monument
A stainless steel post, 28" long, 2½" diam., set 25" in the ground for a reference monument, bears S.60°04'53"E., 16.31 ft., with brass cap mkd. T21S R7W RM ¼4 S27 16.3 FT TO COR 1999 & an arrow pointing to the corner. continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Deposit a magnet in a white plastic case at the base of the stainless steel post.