

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 654)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked  $\frac{1}{4}$  S on N face; from which  
Fir, 20" dia., bears S.18°E., 25 lks., mkd:  $\frac{1}{4}$  S BT.  
Fir, 18" dia., bears N.52°E., 18 lks., mkd:  $\frac{1}{4}$  S BT.

-----  
Wilford N. Haines, #239 - For: Woolley Logging - April 7, 1965 - M 29-67

-----  
Found - Old blazes but no sign of orig.  $\frac{1}{4}$  corner.  
Set - 1"x1"x36" T iron.  
New BTs- 8" Hemlock N.75°E., 6.3 ft.  
11" Hemlock S.72°W., 11.2 ft.

-----  
Douglas Co. Surveyors Office - Gary Langlitz - John E. Nordling - Jan. 16, 1975 - C.S. File 57/17-8

-----  
Found - "T" iron set by Haines in 1965, firmly set from which the only remaining BT marked by Haines:  
An 11" Hemlock now a stump bears S.72°W., 11.2 ft. with scribing " $\frac{1}{4}$ S BT" visible on unhealed blazes.  
Haines NE BT has been completely removed.

At the corner point we set: A 1"x30" iron pipe with brass cap attached mkd:

COUNTY SURVEYORS	T 21 S
OFFICE	$\frac{1}{4}$ $\frac{S 10}{S 15}$
1975	1975

We deposit the "T" iron alongside the brass cap and mark the following BTs

10" Hemlock S.66°W., 55.1 ft., mkd:  $\frac{1}{4}$  S15 CS BT

11" Hemlock N.9°W., 37.0 ft., mkd:  $\frac{1}{4}$  S10 CS BT

This corner is located in a clearcut unit near the top of a small ridge sloping steeply to the NE

Compass decl. 20°E