

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T20-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 571-72)

Set post 4 ft. long, 4" sq. 24" in ground for cor. to secs. 34 & 35, marked T20S R7W on N. face,; S34 on W.; S35 on E. faces, with 2 notches on E. & 4 notches on W. faces; from which

A Maple 12" dia., bears N.62°E., 74 lks. dist. mkd. T20S R7W S35 BT.

A Chinquapin 6" dia., bears S.22°W., 49 lks. dist. mkd. T20S R7W S34 & 35 BT.

A Fir 30" dia., bears N.58°W., 72 lks. dist. mkd. T20S R7W S34 BT.

Wilford Haines - Date unknown - Haines field book, H-64

Found - Old Fir BT, N.58°W., 49 lks. (Dead snag, bark scribed)

Set - Brass cap
6" D.Fir, N.66°W., 84.6 ft., scribed "S.34 T20S R7W BT"
14" D.Fir, S.24¼°W., 94.4 ft., scribed "S.3 T1S R7W BT"

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1159, surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18034)

The Sec. Cor., perpetuated by Haines during an unrecorded survey, year unknown, monumented with a 1" "T" shaped iron rod, firmly set, projecting 6" above ground, with a washer, 1" dia., mkd. Wilford N. Haines 239 Survey Point Drain Oregon, from which the remains of an original bearing tree:

A decayed Chinquapin snag, 18" dia., bears S.22°W., 49 lks. dist., with axe marks visible.

At the corner point

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron rod with alum. cap mkd:

T 20 S R 7 W

S 34 | S 35

S 3

T 21 S R 7 W

1983

from which new bearing trees:

(Cont. next page)

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 462700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T20-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 11" dia., bears N.78½°E., 20 lks. dist. mkd. T20S
R7W S35 BT.
A Fir 10" dia., bears N.38½°W., 28 lks. dist. mkd. X BT.

Fd. OK and used in BLM resurvey by Wayne L. Rogers,
Cadastral Surveyor, Group #1502, surveyed Aug. 1989/Apr.
1991 - (DCSO records Vol. 50 Page(s) 19071-72)

Fd. Ok by Craig Wanless - 9/2005 - M148-50