

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T22-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 632)

-----  
Set post cor. of secs. 2, 3, 34 and 35, from which  
A Maple 8" dia., bears S.34°W., 22 lks. dist.  
A Maple 10" dia., bears N.64°E., 25 lks. dist.  
A Dogwood 4" dia., bears S.66°E., 23 lks. dist.  
A Dogwood 3" dia., bears N.50°W., 57 lks. dist.

Fd. and used in GLO survey by L.H. Wheeler, contract #467, dated April 7, 1883 (DCSO records, Vol. 2 Page 641(

-----  
Wilford N. Haines - For: Harold Woolley - March 1957 - M 4-52

-----  
Point for corner located by proportional measurement.  
Set a 1" x 36" T rod at corner with brass cap inscribed "Wilford N. Haines Survey Point #239"., from which  
30" Fir N.04°30'W., 29.0 ft.  
16" Fir S.75°15'W., 40.9 ft.  
24" Fir S.22°00'E., 46.4 ft.

-----  
Tony Hostetter - For: Seneca Jones Timber Co. - July 2003 - M142-68

-----  
Found - 1" T-post w/brass cap & 3 BTs as described by Haines in 1957 (M4-52)  
New BTs- 32" Fir scribed "S3 NE BT" bears S.24°32'W., 31.2 ft. to spike.