

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 642)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 26, 27, 34, & 35, mkd. T 21 S S 26 on NE, R 7 W S 35 on SE, S 34 on SW, S 27 on NW face, with 2 notches on E & 1 notch on S edges; from which
Dogwood, 4" dia., bears N.54°E., 28 lks., mkd: T21S R7W S26 BT.
Fir, 48" dia., bears S.41°E., 57 lks. mkd: T21S R7W S35 BT
Fir, 20" dia., bears N.65°W., 35 lks. mkd: T21S R7W S27 BT
Yew, 8" dia., bears S.66°W., 32 lks. mkd: T21S R7W S34 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey & S. Bilow - Nov. 25, 1957 - C.S. File 49/20-2

Found - Orig. 20" R.Fir now N.65°W., 23.1 ft. bark scribed "BT T21S"
Orig. 8" now 18" Ewood S.66°W., 21.1 ft. Showed old scar. I open, center rotted, no scribing found. Checks for age.
Also find Orig. 48" now 60" Fir snag. Bark burned, no scribing fd.
All trees check record bearings & distances.
Set brass cap at corner mkd S27S26 T21S R7W COUNTY SURVEYORS
S34S35 OFFICE 1957
New BTs- 8" R.Fir N.14°W. 10.4 ft. scribed S27 T21S R7W CS BT
10" Hemlock S.15½°W., 40.8 ft. scribed S34 T21S R7W CS BT
9" Hemlock N.33°E., 45.6 ft. scribed S26 T21S R7W CS BT.
14" R.Fir S.85°E., 45.2 ft. scribed S35 T21S R7W CS BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #1081 surveyed Sept./Oct. 1981 - (DCSO records Vol. 45 Page(s) 17236-7)

The cor. of secs. 26, 27, 34, & 35, perpetuated & recorded by Byron in 1957, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above the ground, with (properly mkd.) brass cap.
from which the remains of 3 OBTs
A fir stump, 40" dia., bears S.41°E., 57 lks., with no marks visible.
A yew, 19" dia., bears S.71°W., 32 lks., with no scribe marks visible on opened blaze. (Rec. S.66°W.)
continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 48" dia., bears N.61½°W., 35 lks., with no marks visible (Rec. N.65°W.)
and BTs mkd. by Byron
A Hemlock, 20" dia., bears N.34°E., 67½ lks., with healed double blaze.
A Fir, 28" dia., bears S.85°E., 67 lks., with healed double blaze.
A Hemlock, 24" dia., bears S.17°W., 61 lks., with healed double blaze.
A fir, 15" dia., bears N.13½°W., 16 lks., with healed double blaze.

Fd. Ok by Les Roberts 9/1992 - M 115-63
Fd. Ok by Les Roberts 1/29/1997 - C.S. File 65/13-3
Fd. Ok by Les Roberts 5/1999 - M 131-62

FD. ok on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCS0 rec. Vol. 53 page(s) 20634-5)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/11/2019 (filed 11/3/2022) - C.S. File 67/54-34

Reported as Fd OK