

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26 & 27

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 643)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 22, 23, 26, & 27, mkd. T 21 S S 23 on NE, R 7 W S 26 on SE, S 27 on SW, S 22 on NW face, with 2 notches on S & E edges; from which

- Cedar, 6" dia. bears N.54°E., 25 lks. mkd: T21S R7W S23 BT
- Cedar, 10" dia. bears S.80°E. 48 lks. mkd: T21S R7W S26 BT
- Fir, 60" dia. bears N.45°W., 63 lks. mkd: T21S R7W S22 BT.
- Maple, 6" dia. bears S.44°W. 28 lks. mkd: T21S R7W S27 BT

-----  
Wilford Haines - For: E.G. Whipple & Woolley Logging - Feb. 1961 - M20-19

- Set - 1"x1"x36" T. Iron from Orig. N.W. BT. (Now down)
- New BTs- 10" Hemlock S.30°W. 63.7 ft.
- 16" Hemlock S.72°E. 60.9 ft.

-----  
BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20637)

-----  
The cor. of secs. 22, 23, 26, & 27, perpetuated by Haines, in 1961, from original evidence no longer in existence, monumented with a 1" "T" shaped iron rod, firmly set, but badly bent.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, directly over the "T" iron, with brass cap mkd.

T 21 S R 7 W  
S 22 | S 23  
 S 27 | S 26  
 2000

from which bearing trees mkd. by Haines

A hemlock, 27" dia., bears S.72¼°E., 59.5 ft., with a healed blaze.

A hemlock, 23" dia., bears S.30½°W., 64.3 ft., with a healed blaze.

and a bearing tree of no record

A cedar, 45" dia., bears N.37¾°W., 62.0 ft., with healed blaze.

and a new bearing tree

A cedar, 8" dia., bears N.54¼°W., 37.2 ft., mkd. T21S R7W S22 BT.

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26 & 27

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Deposit 2 Mag Nails, at the base of the stainless steel post. Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.