

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 644)

-----

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked 1/4 S on W face; from which Hemlock, 12" dia., bears N.78°E., 22 lks., mkd: 1/4 S BT. Fir, 14" dia., bears N.25°W., 30 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office -John M. Powell - 12/22/1970 - C.S. File 56/12-4

-----

Looked for not found.  
Had good call on top of ridge 5 chains North of corner - line has been run on N-S line with offsets to true line clear cut in Sec. 23.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20639-40)

-----

Point for the 1/4 sec. cor. of secs. 22 & 23, at proportionate distance, there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd.

T 21 S R 7 W  
1/4  
S 22 | S 23  
2000

from which  
A fir, 6" dia., bears S.52 1/4°E., 10.1 ft., mkd. 1/4 S23 BT.  
A fir, 11" dia. bears S.45 1/2°W., 12.2 ft. mkd. 1/4 S22 BT.  
Deposit a magnet in a white plastic case at the base of the stainless steel post.  
Each new bearing tree has a 2 1/2 inch X 1/4 inch magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.