

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 2 Page(s) 645-6)  
-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which  
    Fir, 18" dia., bears N.53°W., 35 lks., mkd: ¼ S BT.  
    Fir, 24" dia., bears S.45°E., 22 lks., mkd: ¼ S BT.

Looked for not found per old visual. Probably DCS0 but no record was found.

Tony Hostetter - For: Roseburg Resources - 9/2023 - M182-79  
-----  
Searched for, not found  
Set - 5/8" Iron rod with aluminum cap marked "T21S R7W ¼ 15 14 LS 1975 2023" At proportionate distance, from which:  
    16" Fir, marked "X", BT tag, bears: N.30°58'E., 23.0 ft to spike.  
    8" Fir, marked "X", BT tag, bears: N.67°28 E., 6.3 ft to spike.  
    55" Fir, marked "X", BT tag, bears: S.35°29'W, 22.7 ft to spike.  
    72" Fir, marked "X", BT tag, bears. N.89°12'W., 20.6 ft to spike.  
Note -BT tags placed on new BTs. list measurements from a 6" spike , placed in the root collar below the "X", to the corner monument.