

PRIMARY CORNER DESCRIPTION Cor. Sec. 10, 11, 14, & 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 2 Page(s) 646)  
-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 10, 11, 14, & 15, mkd. T 21 S S 11 on NE, R 7 W S 14 on SE, S 15 on SW, S 10 on NW face, with 2 notches on E & 4 on S edge; from which  
    Fir, 18" dia. bears N.70°W., 11 lks. mkd: T21S R7W S10 BT.  
    Fir, 18" dia. bears S.11°W., 11 lks. mkd: T21S R7W S15 BT  
    Fir, 12" dia. bears N.72°E., 21 lks. mkd: T21S R7W S11 BT.  
    Fir, 4" dia., bears S.16°E., 95 lks. mkd: T21S R7W S14 BT.

Wilford Haines - July 27, 1955 - C.S. file 42/3 & M1-68  
-----  
Corner set by proportional measurement.  
Set - A 1"x1"x36" angle iron with brass cap inscribed Wilford N. Haines #239, from which  
    A 48" Fir bears N.61°W., 117.0 ft.  
    A 12" Cedar bears S.17°W., 40.0 ft.  
    A 40" Cedar bears N.22°E., 24.0 ft.  
    A 10" Maple bears S.50°E, 10.5 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J Flause - John Pike - April 1992 - C.S File 64/24-11  
-----  
Found - Haines T-Iron, a 1"x1" angle iron with a brass washer mkd: Wilford N. Haines #239, is firmly set and protrudes approx. 10" above ground. (1955)  
Evidence of four bearing trees from Haines resurvey of lines in sec. 10 filed as C.S. 42/3:  
    A 48" Fir now a 54" dia. 4 ft. tall Fir stump with a fully healed double blaze N.64°W., 115.1 ft. (Rec. N.61°W., 117.0 ft., possible a slope dist.)  
    A 12" Cedar now 26" DBH Red Cedar with a partially healed double blaze with illegible scribing visible bears S.15°W., 38.9 ft. (Rec. S.17°W" 40.0 ft., possibly a slope distance)  
    A 40" Cedar now 12 plus foot tall broken Fir snag with a rotted blaze face with no scribing visible bears N.18¼°E., 24.0 ft. (Rec. N.22°E., 24.0 ft.)  
    A fallen burned and broken Maple (Probably BT) lies out of position in SE quadrant from monument.  
New BTs- 17" dia. Hemlock double blazed and scribed "T21S R7W S 11 CS BT" bears N.28°E., 30.0 ft.  
    4" dia. D.Fir double blazed and scribed "X BT" bears S.14°E., 44.6 ft.  
Monument is at corner of clear cuts in SE & NW quadrants. Monument is near bottom of steep westerly slope of canyon which runs N and S.

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Sec. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Oxbow Timber 1 LLC - June 2017 - M173-37  
-----  
Found - Haines T-Iron, Haines' BTs FD:  
A 26" dia. Hemlock bears N.28°E., 30.0'  
A 12" dia. Fir bears S.14°E., 44.6'  
A 29" Cedar bears S.15°W., 38.9'  
A 54" dia., 4' tall fir stump bears N.64°W., 115.1'  
All with healed blazes.  
A six foot steel post is set 2 feet N.85°E.

Tony Hostetter - For: Roseburg Resources - 9/2023 - M182-79  
-----  
Found - 1"x1" angle iron by Haines (Haines 1955, M1-68).  
BTs as described by Edwards in 2017 (M173-37)