

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 647)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which
 Fir, 24" dia., bears N.14°E., 35 lks., mkd: ¼ S BT.
 Fir, 36" dia., bears S.74°E., 35 lks., mkd: ¼ S BT.

Wilford Haines - July 27, 1955 - C.S. file 42/3 & M1-68

Corner set by proportional measurement
Set - A 1"x1"x36" angle iron with brass cap inscribed Wilford
 N. Haines #239, from which
 An 8" D.Fir bears N.62°W., 5.9 ft.
 An 8" D.Fir bears N.73°E., 18.0 ft.

Ken Hoffine - For: Pan-Pacific Forestry - 12/2009 - M160-39

Found - Haines T-iron with washer on top 0.8 feet above ground.
 8" D.Fir snag bears N72½°E., 17.2 ft (rec. N.73°E., 18.0 ft) healed face and tag.
 10" D.Fir bears N.61°W., 5.5 ft (rec N.62°W., 5.9 ft) healed face and tag
Corner lies on steep southwest slope approximately 130 feet north of bottom of draw.

Troy Rambo - For: Seneca Jones Timber Co. - 6/2010 - M160-66

Found - "T" iron per M1-68
 Fd. the record BTs per M160-39
New - Bark scribed "¼ S11 BT" on a 27" pistol butt DF -
 bears S.33°E., 12.5 ft. to a 40D spike at the base of the scribes.
 Set a 6' steel fence post North 1.5 ft.