

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 642)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked  $\frac{1}{4}$  S on N face; from which  
A Fir, 4" dia., bears N.22°E., 11 lks., mkd:  $\frac{1}{4}$  S BT.  
A Fir, 3" dia., bears S.42°E., 32 lks., mkd:  $\frac{1}{4}$  S BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #1081 surveyed Sept./Oct. 1981 - (DCSO records Vol. 45 Page(s) 17236)

-----  
Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground with brass cap marked:

T 21 S R 7 W  
 $\frac{1}{4}$   $\frac{S}{S}$   $\frac{26}{35}$   
1981

from which

A Fir, 22" dia., bears N.51 $\frac{1}{4}$ °E., 48 lks., mkd:  $\frac{1}{4}$  S26 BT.  
A Fir, 29" dia., bears S.35°E., 64 $\frac{1}{2}$  lks., mkd:  $\frac{1}{4}$  S35 BT.

Fd. Ok by Les Roberts 9/1992 - M 115-63