

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 2 Page(s) 644)  
-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on N face; from which  
    Fir, 40" dia., bears South, 64 lks., mkd: ¼ S BT.  
    Maple, 12" dia., bears N.14°E., 37 lks., mkd: ¼ S BT.

Wilford N. Haines - Feb. 17, 1960 - C.S. File 51/67-2  
-----  
Found - Both orig. BTs  
Set - 1"x1"x36" T. Iron.

Wilford Haines - For: E.G. Whipple & Woolley Logging - Feb. 1961 - M20-19  
-----  
Found - 1"x1"x36" T. Iron & 2 orig. BTs.  
        40" Fir snag South 64 lks.  
        12" maple N.14°E., 37 lks.  
New BTs- 12" Fir S.37°W., 10.0 ft.  
        20" Fir N.11°W., 58.8 ft.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Dec. 20, 1984 - C.S. File 62/21-4  
-----  
Found - "T" iron with brass washer set by Haines  
        (Original stone and post not found)  
        40" fir now a snag with bark scribing "BT /4" visible bears S.1½°W., 37.9.ft. (slope dist. 45.7 ft. at 34°) Rec. bearing and distance south 42.2 ft. (Original BT)  
        12" now 23" maple with well healed blaze and Haines washer bears N.14°E., 22.4 ft. (Rec. 24.4 ft.) Level chained. Orig.  
        12" fir now a decayed and dislodged stump with Haines washer and scribing "BT" visible checks well with record S.37°W., 10.0 ft.  
        20" fir now a 28" stump 2 ft. high with single axe mark visible bears N.11°W., 58.8 ft.  
New BTs -13" cedar double blazed and scribed "1/4 S26 CS ET" bears S.57½°E., 53.9 ft.  
        4" Fir double blazed and scribed "1/4 S23 CS BT" bears N.54½°W., 20.1 ft.  
Due to steepness of slope that this monument is on, we did not set a brass cap monument.

Fd. Ok by Les Roberts 9/1992 - M 115-63

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCS0 rec. Vol. 53 page(s) 20638-9)

-----  
The ¼ sec. cor. of secs. 23 & 26, perpetuated by Haines, in 1961, further perpetuated by Monrean, in 1984; monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 8" above ground, with 1 in. brass disc attached to top, with the marks WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of the original bearing trees

A fir snag, 44" diam., bears South, 38.2 ft., with a healed blaze. (Record 42.2 ft.)

A maple, 22" dia., bears N.14°E., 24.4 ft., with a healed blaze.

and bearing trees mkd. by Haines

A roothole, bears S.37°W., 10.0 ft., with a down and decayed fir alongside, size indeterminate, no mks. visible.

A sawed and decayed fir stump, 18" dia., bears N.11°W., 58.8 ft., no marks visible.

and bearing trees mkd. by Monrean

A cedar, 19" dia., bears S.57¾°E., 54.3 ft., with illegible scribe marks visible on partially healed double blaze.

A fir, 14" dia., bears N.53¾°W., 20.1 ft., with a healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, directly over the "T" iron rod, with brass cap mkd.

T 21 S R 7 W

¼ S 23  
S 26

1999

Deposit a magnet in a white plastic case at the base of the stainless steel post.