

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 644-5)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked $\frac{1}{4}$ S on N face; from which
 Fir, 18" dia., bears S.10°E., 17 lks., mkd: $\frac{1}{4}$ S BT.
 Fir, 8" dia., bears N.58°W., 23 lks., mkd: $\frac{1}{4}$ S BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20641)

Point for the $\frac{1}{4}$ sec. cor. of secs. 14 & 23, at proportionate distance, there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 23" in the ground, with brass cap mkd. T 21 S R 7 W

$\frac{1}{4}$ S 14
 S 23
 2000

from which

 A fir, 15" dia., bears N.75 $\frac{3}{4}$ °E., 28.5 ft., mkd. $\frac{1}{4}$ S14 BT.

 A fir, 11" dia., bears S.36 $\frac{1}{2}$ °E., 17.8 ft., mkd. $\frac{1}{4}$ S23 BT.

Each new bearing tree has a 2 $\frac{1}{2}$ " X $\frac{1}{4}$ " magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.

Deposit a magnet in a white plastic case at the base of the stainless steel post.