TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 634)

Set a post, 4" dia., 4 ft. long with marked stone, 12" in the ground, marked ¼ S on W face; from which
A Fir, 4" dia., bears S.38°E., 27 lks., mkd: ¼ S BT.
A Fir, 4" dia., bears S.81°W., 4½ lks., mkd: ¼ S BT.

Wilford Haines - ? - Haines FB H-69

(Possible corner information)
1/4S
5" Fir S.10°W., 24.85
40" Fir N.17°W., 72.00

Wilford Haines - Feb. 1960 - C.S. File 51/67 (C.S. 56/12-3)

Note - These corners set but records lost. (N1/16, W1/4, & S1/16 corners on west line of 36)

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #1081 surveyed Sept./Oct. 1981 - (DCSO records Vol. 45 Page(s) 17233)

The 1/4 sec. cor. of secs. 35 & 36, reestablished by proportionate measurement by Haines in 1960 and accepted as the best available evidence of the position of the orig. corner, monumented with a ¾" "T" shaped iron rod, firmly set, projecting 4" above ground, with an alum. washer mkd. "WILFORD N. HAINES SURVEY POINT 239", from which a BT mkd. by Haines
A Fir, 46" dia., bears N.15¾°W., 94 lks., with scribe marks ¼ S BT visible on bark blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with alum. cap marked: T21S R7W

¼
S 35 | S 36
1981

from which a new BT
A Hemlock, 13" dia. bears S.6½°E., 19½ lks. mkd: ¼ S36 BT.
Deposit the "T" shaped iron rod alongside the alum. post.

Fd. Ok by D. Baker 12/1991 - M 114-36