

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 635-6)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked $\frac{1}{4}$ S on W face; from which
 Fir, 6" dia., bears S.80°W., 25 lks., mkd: $\frac{1}{4}$ S BT.
 Fir, 5" dia., bears N.83°E., 8 lks., mkd: $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office -John M. Powell - 12/23/1970 - C.S. File 56/12-3A

Looked for not found.
Orig. BTs 6"-5" D.Firs -
Found N-S blazed line, Also E-W brushed line which fits call of 7 chains from top of ridge. Timber cut in Sec. 26, however blazed line is back in old timber.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #1081 surveyed Sept./Oct. 1981 - (DCSO records Vol. 45 Page(s) 17235)

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 $\frac{1}{2}$ " dia., 24" in the ground with brass cap marked:

T21S R7W
 $\frac{1}{4}$
 S 26|S 25
 1981

from which
 A Fir, 26" dia., bears N.65 $\frac{1}{4}$ °E., 27 $\frac{1}{2}$ lks., mkd: $\frac{1}{4}$ S25 BT.
 A Fir, 5" dia., bears N.49°W., 24 lks., mkd: $\frac{1}{4}$ S26 BT.

Fd. Ok by L. Roberts 9/1992 - M115-63