



TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

COUNTY SURVEYORS OFFICE  
T 21 S  
S26 S23  
S25 S24  
R 7 W  
1970

from which the remains of original bearing trees  
A sawed fir stump, 84" dia., bears N.45°E., 42.9 ft., with no marks visible.  
A fir, 37" dia., bears N.40°W., 14.5 ft., with a healed blaze.  
and bearing trees mkd. by Powell, in 1970,  
A fir, 11" dia., bears N.46½°E., 23.1 ft., with a healed blaze.  
A fir, 29" dia., bears S.6°E., 40.3 ft., with a healed blaze.  
A fir, 13" dia., bears S.78½°W., 12.9 ft., with a healed blaze.  
Corner is located in a large root hole, on top of a ridge, bears E. and W.

David Edwards - Crew: Brant Miller & Eric Sprinkle - 10/2024  
- C.S. File 65/113-50

-----  
Found - 1970 DCS0 Brass Cap (IP) in good condition.  
A 15" dia. Fir w/healed blaze bears N.46½°E. 23.1'  
A 15" dia. Fir stump w/healed blaze bears S.78½°W., 12.9'  
A 29" dia. Fir snag w/healed blaze bears S.6°E., 40.3'  
A 37" dia. Fir with healed blaze bears N.40°W., 14.51'  
New - A 29" dia. Fir scribed "T21S R7W S25 BT" bears S.87½°E., 45.8'  
A 9" dia. Fir scribed "T21S R7W S26 BT" bears S.87°W., 67.0'  
Note - Compass decl. 15°E.