

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 637)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on W face; from which
Maple, 6" dia., bears S.30°W., 35 lks., mkd: ¼ S BT.
Maple, 10" dia., bears S.15°E., 40 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office -John M. Powell - 12/1970 - C.S. File 56/12-1A

Looked for not found
Found some large Maples, cut into no scribe found.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20631)

Point for the ¼ sec. cor. of secs. 23 & 24, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T 21 S R 7 W
1/4
S 23 | S 24
2000

from which

A fir, 16" dia., bears S.13¾°E., 12.3 ft., mkd. ¼ S24 BT.

A fir, 15" dia., bears S.67½°W., 24.9 ft., mkd. X BT.

Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post.