

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 2 Page(s) 637)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 13, 14, 23, & 24, mkd. T 21 S S 13 on NE, R 7 W S 24 on SE, S 23 on SW, S 14 on NW face, with 1 notch on E & 3 notches on S edges; from which
 Fir, 8" dia., bears S.25°E., 43 lks. mkd: T21S R7W S24 BT.
 Fir, 20" dia. bears S.58°W., 34 lks. mkd: T21S R7W S23 BT
 Fir, 12" dia. bears N.45°E., 54 lks. mkd: T21S R7W S13 BT.
 Fir, 12" dia. bears N.15°W., 31 lks. mkd: T21S R7W S14 BT.

Wilford N. Haines - Feb. 17, 1960 - C.S. File 51/67-2

Found - BT S.58°W., 34 lks.
Set - 1"x1"x36" T. Iron
Scribed- N.14°E., 25.7 ft. (Fir?)

Fd. Ok by Ward, 4/1999 - M 131-54

BLM Dependent resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, under Group #1318, surveyed May/Nov. 1986 - (DCS0 records Vol. 48 Page(s) 18313)

The cor. of secs. 13, 14, 23, & 24, perpetuated & recorded by Haines in 1960, monumented with a 1" T shaped iron rod, firmly set, projecting 4" above ground, from which the remains of an orig. BT:

 A Fir snag, 22" dia., bears S.58°W., 34 lks., no marks visible on opened blaze.
and a BT mkd. by Haines

 A Fir, 52" dia., bears N.18°E., 40 lks., with scribe marks T21S R7W S13 BT visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, directly over T iron, with brass cap marked:

 T 21 S R 7 W
 S 14 | S 13
 S 23 | S 24
 1986

from which new BTs

 A Fir, 8" dia. bears S.73°E., 67 lks. mkd: T21S R7W S24 BT

 A Fir, 6" dia. bears N.85°W., 44 lks. mkd: T21S R7W S14 BT

No other suitable trees available.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. Ok by Ward 4/1999 - M 131-54

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCS0 rec. Vol. 53 page(s) 20632)

The cor. of secs. 13, 14, 23, & 24, monumented with a iron post, 2½" diam., firmly set, projecting 3" above ground, with brass cap mkd.

T 21 S R 7 W
S 14 | S 13
S 23 | S 24
1986

from which the remains of an original bearing tree
A decayed fir snag, 22" diam., bears S.58°W., 22.4 ft., no marks visible.

and a bearing tree mkd. by Haines, in 1960,
A fir, 57" diam., bears N.18°E., 26.4 ft., with scribe marks T21SR7WS13BT visible on the bark.

and bearing trees mkd. by Rogers and Robb
A fir, 12" diam., bears S.73°E., 44.2 ft., with a healed blaze.

A fir, 11" diam., bears N.85°W., 29.0 ft., with a healed blaze.
and a new bearing tree

A fir, 13" diam., bears S.70½°W., 5.6 ft., mkd. X BT.
Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description