

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 638)

-----  
Set stake, 5" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which  
Fir, 8" dia., bears S.85°E., 16 lks., mkd: ¼ S BT.  
Fir, 24" dia., bears S.15°W., 8 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20633)

-----  
The ¼ sec. cor. of secs. 13 & 14, determined at record bearing & distance from the remains of an original bearing tree.

A sawed and decayed fir stump, 28" dia., bears S. 15° W., 5.3 ft., with fragmentary scribe marks visible on an opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T 21 S R 7 W  
1/4  
S 14 S 13  
2000

from which new bearing trees

A fir, 11" dia., bears N.48½°E., 21.4 ft., mkd. ¼ S13 BT.

A fir, 10" dia., bears N.30½°W., 13.6 ft., mkd. ¼ S14 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.