

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 638-9)

-----  
Set post, 5" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 11 & 12, 13 & 14, mkd. T 21 S S 12 on NE, R 7 W S 13 on SE, S 14 on SW, S 11 on NW face, with 1 notch on E & 4 notches on S edge; from which

- Fir, 20" dia. bears S.68°E., 18 lks. mkd: T21S R7W S13 BT.
- Fir, 20" dia. bears S.30°W. 17 lks. mkd: T21S R7W S14 BT.
- Fir, 6" dia., bears N.50°W., 33 lks. mkd: T21S R7W S11 BT.
- Fir, 3" dia., bears N.40°E., 75 lks. mkd: T21S R7W S12 BT.

-----  
Wilford N. Haines - For: Woolley Logging - Dec. 1961 - M21-73

- Found - 20" Fir, now 36", S.30°W., 17 lks.
- Set - 1"x1"x36" T. iron & scribed:
  - 8" D.Fir N.16°E., 42.2 ft.
  - 8" D.Fir N.70°W., 20.7 ft.

-----  
BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1916, surveyed Aug. 1999/May 2000. (DCSO rec. Vol. 53 page(s) 20633-4)

-----  
The cor. of secs. 11, 12, 13, & 14, perpetuated by Haines, in 1961, monumented with a 1" "T" shaped iron rod, firmly set, projecting 4" above ground, from which the remains of an original bearing tree

A sawed and decayed fir stump, 35" diam., bears S.30°W., 11.2 ft., with no scribe marks visible on opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T 21 S R 7 W	
<u>S 11</u>	<u>S 12</u>
S 14	S 13

2000 and new BTs

- A fir, 7" dia. bears N.7¾°E. 35.6 ft. mkd. T21S R7W S12 BT
- A fir, 10" dia. bears S.59½°E. 11.6 ft. mkd. T21S R7W S13 BT
- A fir, 5" dia., bears S.10°W., 8.1 ft., mkd. X BT.
- A fir, 11" dia. bears N.67°W. 42.8 ft. mkd. T21S R7W S11 BT

Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise described in the corner description.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

-----  
continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found BC & 5 BTs by Ron Rice, 7/2006 - M151-15. All BTs have red painted band & face plus BT tag. Galvanized post set adjacent to corner monument.