TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 639)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 36" dia., bears S.30°W., 38 lks., mkd: ¼ S BT.
Fir, 30" dia., bears S.43°E., 54 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging - Dec. 1961 - M21-73

Found - 2 orig. BTs: 36" Fir, now 40" S.30°W., 38 lks.
30" Fir, now 36" S.43°E., 54 lks.
Set - 1"x1"x36" T iron & marked:
¼ S BO on rock face S.67½°W., 47.4 ft.

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 7/2006 - M 151-15

Found - 1" T iron
34" D.Fir bears S.43°E., 35.6' - healed face.
Rock face marked ¼ S11 X bears S.67½°W., 47.4', rec 36" D.Fir S.30°W., 38 lks - down out of position
New BT - 9" D.Fir bears N.71½°W., 28.8', blazed, scribed, ¼ S11 BT
All BTs have red painted band and face plus BT tag. X S11 BO painted red and galvanized post set adjacent to corner monument.