

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 640)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 1, 2, 11, & 12 mkd. T 21 S S 1 on NE, R 7 W S 12 on SE, S 11 on SW, S 2 on NW face, with 5 notches on S & 1 on E edges; from which

Fir, 16" dia., bears N.11°E., 19 lks. mkd: T21S R7W S1 BT.

Fir, 16" dia. bears S.52°E., 11 lks. mkd: T21S R7W S12 BT.

Fir, 16" dia. bears S.56°W., 47 lks. mkd: T21S R7W S11 BT

Fir, 10" dia., bears N.33°W., 28 lks. mkd: T21S R7W S2 BT.

Wilford N. Haines - May 1961 - C.S. File 51/67-2

All the orig. BTs have been dead for many years. None healed over.

Found - 10" Fir N.33°W., 28 lks., (now stub 1 ft. ht., no scribe)

16" Fir N.11°E., 19 lks., (now down & rotten)

16" Fir S.56°W., 47 lks., (now stub 1 ft. ht. fd. scribe BT)

16" Fir S.52°E., 11 lks., (now down, fd. scribe T21S R7W)

Set - 1"x1"x36" T iron.

Marked X B0 on rock face 20 ft. wide x 8 ft. ht. S.17½°W., 25.4 ft.

Scribed 14" Hemlock N.43½°E., 10.8 ft.

Someone has marked a 36" Fir ± S11 TXXI5 RVIIW S.80°W. ± about 50 ft. Used a pocket knife about 15-20 years ago.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1658, surveyed Aug./Sept. 1992 - (DCSO records Vol. 51 Page(s) 19272-3)

The cor. of secs. 1, 2, 11 and 12, perpetuated & recorded from original evidence no longer in existence by Haines, in 1961, monumented with a "T" shaped iron rod, 1" dia., firmly set, extending 3" above the ground, with a brass disk mkd. WILFORD N. HAINES LS 239 DRAIN OREGON, from which a bearing tree and a bearing object mkd. by Haines:

A hemlock, 23" dia., bears N.41½°E., 16 lks., with a healed blaze.

A rock face, 20 ft. wide x 8 ft. high, bears S.17°W., 38 lks. to X, with marks XB0 visible.

and the remains of a bearing tree mkd. by person(s) unknown and reported by Haines

continued next page

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir stump, 37" dia., bears S.69¼°W., 73 lks., with scribe marks S11 TXX1 BT visible on the bark.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.

T21S		R7W	
S 2		S 1	
S 11		S 12	
1992			

from which a new bearing tree

A fir, 8" dia. bears S.63½°E. 30 lks. mkd. T21S R7W S12 BT
No suitable bearing trees available within limits northwest of the corner.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this corner, the BLM Geodetic Control Station No. EC 41164, at latitude 43° 45' 44.50" N., longitude 123° 29' 24.41" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S. 87° 00' 00" W., 18.800 chs. (mean bearing and sea level distance), monumented with an aluminum cap, 3" dia., set in cement flush with the ground, mkd. EC 41164 GPS 1992. The station is on the easterly edge of a gravel road, 30 lks. wide, bearing N. and S.

Found BC & 3 BTs by Ron Rice, 7/2006 - M151-15. All BTs have red painted band & face plus BT tag. X B0 painted red & galvanized post set adjacent to corner monument.