

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION C C for secs. 1 & 2 (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 554-55)

Set post 6" dia., 4 ft. long, 24" in ground, for closing cor. to secs. 1 & 2, marked on N., T20S R7W S36; on the SE., R7W S1; on the SW. face, T21S S2; with 1 notch on the E. and 5 on the W. edges; from which
A Fir 10" dia., bears N.65°E., 26 lks. dist. mkd. T20S R7W S36 BT.
A Fir 16" dia., bears S.6°E., 42 lks. dist. mkd. T21S R7W S1 BT.
A Fir 16" dia., bears S.63°W., 12 lks. dist. mkd. T21S R7W S2 BT.

Fd. and used in GL0 Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 570)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - and crew - May 2, 1962 - C.S. File 49/20-15

Found - Haines "T" iron, no cap.
30" Fir, S.6°E., 27.7 ft., has been previously opened, scribing visible on old face, mostly illegible.
Stump, N.65°E., 17.2 ft. Cut too low to find scars or scribing.
No trace of SW. BT.
New BT - 17" D.Fir S.62½°W., 67.8 ft. mkd. T21S R7W CC S2 CS BT.
Haines has rescribed 30" Fir, S.6°E., 27.7 ft. "S1 BT" in bark.

Harvey Christensen, survey for Seneca Jones Timber Co. Sept. 1998 - M130-35

Found - Haines "T" post 0.8 ft. above ground.
-18" D.Fir, S.62°W., 67.8 ft. stump w/tin cap, healed face
-30" D.Fir, S.6°E., 27.7 ft. stump w/tin cap, open w/scribing visible
New Accessories -
16" D.Fir, N.68°E., 41.2 ft. blazed & scribed "X BT"
7" D.Fir, S.82°E., 32.0 ft. blazed & scribed "X BT"
19" R.Alder, N.78°W., 29.8 ft. bark scribed "X BT"
Set 5 ft. steel post 1 foot West.