

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 622700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only, T20-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 569-70)

-----  
Set post 4 ft. long, 4" sq., 2 ft. in ground, for ¼ sec. cor. mkd. ¼ S on N. face, from which

A Maple 8" dia., bears S.34°E., 26 lks. dist. mkd. ¼ S BT.

A Fir 28" dia., bears N.12°W., 20 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C. Putnam, crew - May 1962 - C.S. File 49/20-14

-----  
Found - Haines "T" Iron and cap at corner.

Fir stump, now 36", N.12°W., 13.2 ft., previously chopped open & good scribing "¼" visible on old face.

No trace of SE. BT. Area has been clear cut. No live trees near.

New BT - 36" Fir stump, N.38°E., 27.2 ft. mkd. ¼ S36 CS BT. Stumps are badly charred but otherwise in good condition.

Harvey Christensen, survey for Seneca Jones Timber Co. Sept. 1998 - M130-35

-----  
Found - Haines "T" post with cap 1.0 ft. above ground.

- 36" D.Fir, N.12°W., 13.2 ft. stump w/old scribing

- 36" D.Fir, N.38°E., 27.2 ft. stump w/old scribing

New Accessories -

11" D.Fir, N.71°W., 13.3 ft. blazed & scribed "¼ S36 BT"

9" D.Fir, N.16°E., 17.8 ft. blazed & scribed "¼ S36 BT"

14" D.Fir, S.12°E., 12.7 ft. blazed & scribed "X BT"

8" D.Fir, S.35°W., 15.7 ft. blazed & scribed "X BT"

Set 5 ft. steel post 1 foot West.