

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 1 of T22-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 631)

Set qr. sec. post; from which
A Fir 36" dia., bears N.38°E., 29 lks. dist.
A Fir 36" dia., bears S.30°W., 40 lks. dist.

BLM resurvey, by Boyd W. Peterson, under special instructions dated August 18, 1986, under Group #1346, Surveyed Sept./Dec. 1986 (DCSO records Vol. 48 Page(s) 18306-07)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an stainless steel post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

T 21 S R 7 W
¼ S 36
S 1
S 22 S
1986

from which
A Fir 17" dia., bears S.31½°W., 10 lks. dist. mkd. ¼ S1 BT
A Fir 21" dia., bears N.14½°W., 15 lks. dist. mkd. ¼ S36 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. OK, Dec. 1991, D. Baker, M 114-26