

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 635)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked $\frac{1}{4}$ S on N face; from which
Fir, 48" dia., bears S.15°E., 39 lks., mkd: $\frac{1}{4}$ S BT.
Willow, 8" dia., bears N.10°E., 28 lks., mkd: $\frac{1}{4}$ S BT.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1496, surveyed July/Aug. 1989 - (DCSO records Vol. 50 Page(s) 18949)

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 & 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " diam., 22" in the ground, with brass cap mkd.

T 21 S R 7 W

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{25}{36}$
1989

from which

A fir, 11" diam., bears N. 18° E., 27 lks., mkd. $\frac{1}{4}$ S25 BT.

A fir, 9" diam., bears S. 72° W., 19 lks., mkd. $\frac{1}{4}$ S36 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is at the top of ascent, slopes S.