

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 636)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on N face; from which  
A fir, 20" dia., bears N.80°E., 20 lks., mkd: ¼ S BT.  
A fir, 18" dia., bears S.14°W., 32 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office -John M. Powell - 12/22/1970 - C.S. File 56/12-4

-----  
Looked for not found.  
Found scribed Dogwood "¼S"  
Also scribed post "¼S"  
D.Fir faced(?) up no scribing visible.  
This corner found in the 50's by forest appraisal no record of this cor. - orig. cor. not found - calls on orig. notes don't jibe up with ground.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1496, surveyed July/Aug. 1989 - (DCSO records Vol. 50 Page(s) 18951)

-----  
S. 87° 14' 30" W., bet. secs. 24 and 25.  
40.115 chains  
Point selected for a witness cor. to the ¼ sec. cor. of secs. 24 & 25.  
Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd.

W C  
T 21 S R 7 W  
¼  $\frac{S\ 24}{S\ 25}$   
1989

from which  
A fir, 15" diam., bears N. 42° E., 29 lks., mkd. X at breast height and BT at the base.  
A fir, 12" diam., bears S. 8° W., 5 lks., mkd. X at breast height and BT at the base.

40.615 chains  
True point for the ¼ sec. cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the original corner; located on steep rock outcrop, sloping NE., where it is impracticable to establish a permanent monument.