

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 638)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked $\frac{1}{4}$ S on W face; from which
A Fir, 8" dia., bears S.18°E., 17 lks., mkd: $\frac{1}{4}$ S BT.
A Fir, 12" dia., bears N.27°W., 42 lks., mkd: $\frac{1}{4}$ S BT.

BLM Dependent resurvey by Wayne Rogers & Joel Robb, Cadastral Surveyors, under Group #1318, surveyed May/Nov. 1986 - (DCSO records Vol. 48 Page(s) 18312-3)

Point for the $\frac{1}{4}$ sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 $\frac{1}{2}$ " dia., 22" in the ground with brass cap marked:

T 21 S R 7 W
 $\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$
1986

from which

A Fir, 4" dia., bears S.5°W., 50 lks., mkd: X BT.
A Cedar, 37" dia., bears N.19°W., 72 lks., mkd: $\frac{1}{4}$ S13 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.