TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 639)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
Fir, 12" dia., bears N.21°E., 24 lks., mkd: ¼ S BT.
Fir, 14" dia., bears S.15°W., 70 lks., mkd: ¼ S BT.

Wilford N. Haines - For: Woolley Logging - Dec. 1961 - M21-73

Found - No trace of orig. ¼ sec. corner.
Set - 1"x1"x36" T iron
16" Fir S.53°E., 50.7 ft.
12" Fir N.51½°E., 75.7 ft.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - Jan. 14, 1974 - C.S. File 56/43-2

Found - 1"x1"x36" T iron in place & bent. (1961)
16" now 20" D.Fir, bears S.53°E., 50.4 ft. (rec. S.53°E. 50.7 ft.) I open & find good scribing "3"
Rec. 12" D.Fir, now down & burned, bears N.71°E., 72.6 ft. (Rec. N.51½°E. 75.7 ft) Blaze burnt out. This tree may not be in its rec. position due to logging activity.
Set Brass cap alongside T iron mkd: COUNTY SURVEYORS OFFICE 1974 ¼ T21S S 12 / S 13 R7W
(set flush with ground)
New BTs- 20" D.Fir bears N.11°E. 115.6 ft scribed ¼ S12 CS BT
Note - This corner lies on steep north slope in recent logged over area.
4/24/1974
Set steel fence post alongside brass cap.

Found BC & 2 BTs by Ron Rice, 7/2006 - M151-15. All BTs have red painted band & face plus BT tag. Steel post adjacent to corner monument with survey marked placard.