

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 640)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked $\frac{1}{4}$ S on N face; from which
Fir, 14" dia., bears N.18°E., 25 lks., mkd: $\frac{1}{4}$ S BT.
Fir, 40" dia., bears S.13°W., 80 lks., mkd: $\frac{1}{4}$ S BT.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1658, surveyed Aug./Sept. 1992 - (DCSO records Vol. 51 Page(s) 19272)

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 & 12, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 22" in the ground, and in a mound of stone 2 $\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T21S R7W
 $\frac{1}{4}$ $\frac{S \ 1}{S \ 12}$
1992

from which

A fir, 8" dia., bears N.46°E., 3 $\frac{1}{2}$ lks. , mkd. $\frac{1}{4}$ S1 BT.

A fir, 9" dia., bears S.46°W., 18 lks. , mkd. $\frac{1}{4}$ S12 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.