

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION N 1/4 Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 554)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked $\frac{1}{4}$ S on N face; from which
A fir, 24" dia., bears N.28°E., 12 lks., mkd: $\frac{1}{4}$ S BT.
A fir, 24" dia., bears S.32°W., 49 lks., mkd: $\frac{1}{4}$ S BT.

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 569)

A post, 4" sq., firmly set in the ground, 2 ft. in ground, for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ S on N. face, for $\frac{1}{4}$ sec. cor. to sec. 1; from which
A fir, 24" dia., bears N.28°E., 12 lks., mkd: $\frac{1}{4}$ S BT.
A fir, 24" dia., bears S.33°W., 49 lks., mkd: $\frac{1}{4}$ S BT.

Reported as not found on previous corner renewal visual page. Probably by the County Surveyor's Office in the late 1950's or the 1960's. No record of report found. (Milo Godfrey and crew was in the area in the spring of 1962.)
DCSO JC - 6/3/2002