

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 549)

-----  
A Hemlock 8" dia. for qr. sec. cor. marked ¼ S on West face, from which

A Fir 40" dia., bears S.71°W., 54 lks. dist. mkd. ¼ S BT.

A Fir 18" dia., bears S.30°E., 5 lks. dist. mkd. ¼ S BT.

-----  
Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

-----  
Found old BTs, very rotten.

Scribed:

40" Fir N.53°W., 28.4 ft.

6" Hemlock N.31°W., 16.8 ft.

-----  
Douglas Co. Surveyors Office - John M. Powell, and crew - April 1972 - C.S. File 56/12

-----  
Found - 40" D.Fir, down, N.53°E., (Rec. N.53°W.) 28.4 ft. scribe visible.

6" Hemlock now 10", N.31°W., 16.8 ft., shows good scar.

Haines T iron at ¼ corner.

New BT - 7" Hemlock S.54°E., 24.0 ft. scribed ¼ S31 CS BT.

-----  
BLM resurvey by Wayne L. Rogers; Dale T. Bedell; Cadastral Surveyors - under Group #1392, surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18463)

-----  
The ¼ sec. cor. perpetuated and recorded by Haines in 1960, and further perpetuated and recorded by Powell in 1972, monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 3" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE., from which the remains of an original bearing tree:

A rotted Fir stump 16" dia., bears S.30°E., 5 lks. dist., no marks remaining.

and bearing trees mkd. by Haines:

A rotted Fir stump size indeterminate, bears N.53°E., 38½ lks. dist., no marks remaining.

A Hemlock 18" dia., bears N.31°W., 25 lks. dist. with healed blaze.

and a bearing tree mkd. by Powell:

A Hemlock 14" dia., bears S.54°E., 36 lks. dist., with scribe marks ¼ S31 CS visible on a partially healed blaze.

(Cont. Next Page)

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

At the corner point  
Set an stainless steel post, 28" long, 2 1/2" dia., 22" in  
the ground, directly over the iron rod, with brass cap mkd:

T 21 S  
R 7 W R 6 W  
S 36 | <sup>1/4</sup>S 31  
1987

Deposit white "DEEP-1" magnetic marker at base of stainless  
steel post.

Fd. OK Dec. 1991 by D. Baker - M 114-26

David Edwards - For: Seneca Jones Timber Co. - Nov 2012 -  
C.S. File 65/75-11

-----  
Found - Brass cap  
24" hemlock S.53°E., 23.6'  
20" hemlock N.30W., 16.4'  
Both with healed blaze  
Steel fence post 2' south