

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30, T21-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 550)

-----  
Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for qr. sec. cor., marked  $\frac{1}{4}$  S on West face; from which  
A burnt Fir 50" dia., bears S.87°E., 77 lks. dist. mkd.  $\frac{1}{4}$  S BT.  
A burnt Fir 24" dia., bears N.87°W., 169 lks. dist. mkd.  $\frac{1}{4}$  S BT.

Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

-----  
Set 1" x 1" x 36" T. Iron, from which scribed  
10" Fir, N.08°W., 2.7 ft.  
10" Fir, S.46°E., 2.1 ft.

BLM Resurvey by Wayne L. Rogers and Dale T. Bedell, Cadastral Surveyors, under Group #1392, surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18465)

-----  
The  $\frac{1}{4}$  sec. cor., reestablished by proportionate measurement and recorded by Haines in 1960; there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 4" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE., from which the remains of bearing trees mkd. by Haines:

A Fir 13" dia., bears S.40°E., 3 $\frac{1}{2}$  lks. dist. with healed blaze.

A Fir snag, 10" dia., bears N.10°W., 4 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron rod, with brass cap mkd:

T 21 S  
R 7 W R 6 W  
 $\frac{1}{4}$   
S 25 | S 30  
1987

from which a new bearing tree

A Fir 19" dia., bears N.61°W., 24 lks. dist. mkd.  $\frac{1}{4}$  S25 BT.