

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 550)

St post 5" dia., 4 ft. long, with marked stone, 12" in ground for cor. secs. 24, 25, 19 and 30, marked T21S S19 on NE.; R6W S30 on SE.; R7W S25 on SW.; S24 on NW. face, with two notches on the S. and four on the N. edge; from which

A Fir 30" dia., bears S.50°W., 43 lks. dist. mkd. T21S R7W S25 BT.

A Fir 30" dia., bears N.46°W., 94 lks. dist. mkd. T21S R7W S24 BT.

A Fir 30" dia., bears S.20°E., 15 lks. dist. mkd. T21S R6W S30 BT.

An Alder 10" dia., bears N.17°E., 25 lks. dist. mkd. T21S R6W S19 BT.

Wilford N. Haines, #239 - Filed Feb. 17, 1960 - C.S. File 51/67-2

Set 1" x 1" x 36" T. iron from which scribed

8" Fir N.56°W., 11.7 ft.

6" Fir N.29°E., 7.4 ft.

8" Fir S.01°E., 1.7 ft.

8" Fir S.78°W., 17.8 ft.

BLM resurvey by Wayne L. Rogers and Dale T. Bedell, Cadastral Surveyors, under Group #1392, surveyed Aug/Nov. 1987 - (DCSO records Vol. 48 Page(s) 18466)

The Sec. Cor., reestablished by proportionate measurement and recorded by Haines in 1960; there is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with a "T" shaped iron rod, 1" dia., firmly set, projecting 4" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE., from which the bearing trees mkd. by Haines:

A Fir 12" dia., bears N.30°E., 11 lks. dist. with healed blaze.

A Fir 18" dia., bears S.1°E., 3 lks. dist. with healed blaze.

A Fir 15" dia., bears S.72°W., 27 lks. dist. with healed blaze.

A Fir 13" dia., bears N.56°W., 18 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, directly over the iron rod, with brass cap mkd:

(Cont. Next Page)

TOWNSHIP 21 RANGE 07 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 21 S	
R 7 W	R 6 W
S 24	S 19
S 25	S 30
1987	

Fd. OK, and used in BLM Resurvey by Dale T. Bedell, under Group #1496, Surveyed July/Aug. 1989 - (DCSO records Vol. 50 Page(s) 18950)